




GF25 ErP WALL HEATER



Device model:	GF25F ErP		GF25P ErP	
Fuel	Natural gas	LP gas	Natural gas	LP gas
Max. rated heat output (kW)	2.95	3.0	2.9	2.9
Efficiency (%)	95	95	94	93
Energy efficiency class:	B		C	
Space heated (m ³):	40-70			
Height (mm)	700			
Depth (mm)	310	395		
Width (mm)	500			
Weight (kg)	20	20		
Gas connection	G1/2"			
Flue outlet type	direct vent	chimney.		
Flue outlet diameter (mm)	97	76		
Material of combustion chamber	steel			
Colours	beige			

GF30 ErP WALL HEATER

Device model:	GF30F ErP		GF30P ErP	
Fuel	Natural gas	LP gas	Natural gas	LP gas
Max. rated heat output (kW)	3.0	3.1	2.9	2.9
Efficiency	94	95	85	88
Energy efficiency class	B		C	
Space heated (m ³):	40-70			
Height (mm)	685	660		
Depth (mm)	310	440		
Width (mm)	500			
Weight (kg)	34	34		
Gas connection	G1/2"			
Flue outlet type	direct vent	chimney		
Flue outlet diameter (mm)	97	76		
Material of combustion chamber	casting			
Colours	beige			



LIABILITY • ENERGY EFFICIENCY • GUARANTEE

